

# Terminal Profile

<https://apple.stackexchange.com/questions/282185/how-do-i-get-different-colors-for-directories-etc-in-item2>

```
osascript "/Volumes/GoogleDrive/My Drive/Scripts/osx/RandomColoriTerm2.scpt"

# Tell ls to be colourful
export CLICOLOR=1
export LSCOLORS="GxfxcxdxBxegecabagacad"

echo "colorscheme desert" > ~/.vimrc

# Tell grep to highlight matches
export GREP_OPTIONS='--color=auto'

# Other practical exports

export EDITOR=vim
export HISTCONTROL=erasedups
export HISTSIZE=10000

#Works only for bash
#shopt -s histappend

# Color in Maven
alias maven="command mvn"
color_maven() {
  maven $* | sed -e "s/\(\([INFO\]\) \-.*\)/[36;01m\1[m/g" \
    -e "s/\(\([INFO\]\) >>> .* \)/[32;01m\1[m/g" \
    -e "s/\(\([INFO\]\) <<< .* \)/[32;01m\1[m/g" \
    -e "s/\(\([INFO\]\) Building .* \)/[36;01m\1[m/g" \
    -e "s/\(\([INFO\]\) \[.*\)/01m\1[m/g" \
    -e "s/\(\([INFO\]\) BUILD SUCCESS\)/[01;32m\1[m/g" \
    -e "s/\(\([INFO\]\) BUILD FAILURE\)/[01;31m\1[m/g" \
    -e "s/\(\([WARNING\]\).* \)/[01;33m\1[m/g" \
    -e "s/\(WARN.* \)/[01;33m\1[m/g" \
    -e "s/\(DEBUG.* \)/[01;33m\1[m/g" \
    -e "s/\(\([ERROR\]\).* \)/[01;31m\1[m/g" \
    -e "s/Tests run: \([^\,]*\), Failures: \([^\,]*\), Errors: \([^\,]*\), Skipped: \([^\,]*\)/[32mTests
run: \1[m, Failures: [01;31m\2[m, Errors: [01;31m\3[m, Skipped: [01;33m\4[m/g"
}
alias mvn=color_maven

#Color in man pages
man() {
  env \
    LESS_TERMCAP_mb=$(printf "\e[1;31m") \
    LESS_TERMCAP_md=$(printf "\e[1;31m") \
    LESS_TERMCAP_me=$(printf "\e[0m") \
    LESS_TERMCAP_se=$(printf "\e[0m") \
    LESS_TERMCAP_so=$(printf "\e[1;44;33m") \
    LESS_TERMCAP_ue=$(printf "\e[0m") \
    LESS_TERMCAP_us=$(printf "\e[1;32m") \
  man "$@"
}

### Startup messages
echo "Welcome to "`scutil --get ComputerName`/"`ipconfig getifaddr en0` "["`sw_vers -productName`@"`sw_vers -
productVersion`"]"
```